

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number  
**WO 2005/093198 A2**

(51) International Patent Classification<sup>7</sup>: **E06B 9/323**, 9/64

(21) International Application Number:

PCT/EP2005/003753

(22) International Filing Date: 17 March 2005 (17.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

1025790 22 March 2004 (22.03.2004) NL

1028053 18 January 2005 (18.01.2005) NL

(71) Applicant and

(72) Inventor: **ROETGERING, Grit** [NL/NL]; Goorseweg  
27, NL-7468 SH Enter (NL).


(74) Agent: **SHUMANN, Bernard, Herman, Johan**; Schu-  
mann Patent Consultancy B.V., Kerkedennen 43, NL-7621  
EB Borne (NL).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PROFILED BAR WITH A RAISING MECHANISM FOR A WINDOW OR DOOR COVERING



(57) Abstract: A bar intended for fixing to the topside of a window or door comprises: a first cavity for accommodating a raising mechanism for raising cords for a covering for the window, which internal cavity is accessible from outside via holes in the bar for passage of a control cord and at least two cords which are connected for driving to the underside of the covering; a second cavity which extends in the longitudinal direction and which debouches via a constriction onto the outside of the bar, and serves to receive the upper edge of the covering which fits into the second cavity but is too wide to pass through the constriction; two profiles which together bound the first cavity, in at least one of which profiles said holes are present.

WO 2005/093198 A2



**Published:**

— without international search report and to be republished  
upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*